

SURFACE MOUNT PLANTER 40

SURFACE MOUNTED FREESTANDING HVM PROTECTION



PRODUCT OVERVIEW

SAFETYFLEX'S DESIGN TEAM HAVE CREATED AN INNOVATIVE SURFACE MOUNT SOLUTION THAT IS CAPABLE OF OFFERING INSTANT PROTECTION FROM HOSTILE VEHICLE ATTACKS. THE SURFACE MOUNTED PLANTER 40 IS COMPLETELY FREESTANDING, WITH NO REQUIREMENT FOR CIVIL WORKS OR PINNING TO SURFACE, ALLOWING FOR QUICK INSTALLATION & RELOCATION AS REQUIRED AT A FRACTION OF THE COST OF TRADITIONAL METHODS.

OUR UNIQUE PATENTED DESIGN HAS BEEN INDEPENDENTLY CRASH TESTED IN ACCORDANCE WITH IWA -14 TO ARREST A 7.2 TONNE VEHICLE TRAVELLING AT 40 MPH /64KPH. THE SURFACE MOUNT PLANTER CAN BE USED AS TEMPORARY, PERMANENT OR TRANSIENT MEASURE.

THE SURFACE MOUNT PLANTER 40 CAN ACCEPT A RANGE OF AESTHETIC ENHANCEMENTS, INCLUDING BESPOKE CLADDING TO ENABLING IT TO BLEND SEAMLESSLY WITH THE BUILT ENVIRONMENT AND NUMEROUS STREET FURNITURE OPTIONS.

FINISHES

STANDARD CONCRETE FINISH WITH OPTION TO CLAD IN ALTERNATIVE FINISHES. PLEASE CONTACT YOUR SALES REPRESENTATIVE FOR MORE DETAILS.

APPLICATIONS

- > PUBLIC REALM
- > STADIA
- > RETAIL PARKS
- > LEISURE ATTRACTIONS
- > CRITICAL INFRASTRUCTURE
- > POLICE STATIONS
- > GOVERNMENT BUILDINGS
- > DATA CENTRES
- > SHOPPING CENTRES
- > AIRPORTS

SURFACE MOUNT PLANTER 40 SPECIFICATION DETAILS

BLOCK MEASUREMENTS	2000MM W X 1200MM D X 870MM H
BLOCK CENTRES	3200MM CENTRES, 1200MM AIR GAP
DRAINAGE METHOD	TWO DRAINAGE TUBES LOCATED WITHIN THE BLOCK
CRASH TEST RATING	IWA 14-1:2013 V/7200[N2A]/64/90:5.3
SEATING HEIGHT	430MM
PLANTING DEPTH	200MM
MINIMUM ARRAY	ONE BLOCK

REVISION

00/2023

SURFACE MOUNT PLANTER 40

SURFACE MOUNTED FREESTANDING HVM PROTECTION

safetyflex
ANTI TERRORIST BARRIERS



REVISION

00/2023

ALL PHOTOS USED FOR ILLUSTRATION PURPOSES ONLY. ALL DIMENSIONS +/- 5%

safetyflex
ANTI TERRORIST BARRIERS

EMAIL: INFO@SAFETYFLEXBARRIERS.COM |
TELEPHONE: + 44 (0) 2476 662 116 |
WEBSITE: WWW.SAFETYFLEXBARRIERS.COM